HUNTEC



SWITCHING POWER SUPPLY

Product Guide

RPS-C1-... series Din Rail Power Supply



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -10~+50℃
- Dimension 32*125.2*102MM
- Weight 0.51KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C1-75-12	12V	6.3A	85%
RPS-C1-75-24	24V	3.2A	88%
RPS-C1-75-36	36V	2.1A	89%
RPS-C1-75-48	48V	1.6A	89%



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -10~+50℃
- Dimension 40*125.2*113.5MM
- Weight 0.6KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C1-120-12	12V	10A	85%
RPS-C1-120-24	24V	5A	88%
RPS-C1-120-36	36V	3.4A	89%
RPS-C1-120-48	48V	2.5A	89%



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -10~+50℃
- Dimension 63*125.2*113.5MM
- Weight 1KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C1-240-24	24V	10A	88%
RPS-C1-240-36	36V	6.6A	89%
RPS-C1-240-48	48V	5A	89%
RPS-C1-240-60	60V	4A	90%



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -10~+50℃
- Dimension 85.5*125.2*128.5MM
- Weight 1.5KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C1-480-24	24V	20A	92%
RPS-C1-480-36	36V	13.3A	92%
RPS-C1-480-48	48V	10A	92%
RPS-C1-480-60	60V	8A	92%

RPS-C2-... Series Din Rail Power Supply



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -10~+50℃
- Dimension 22.5*90*100MM
- Weight 0.17KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C2-10-5	5V	2A	77%
RPS-C2-10-12	12V	0.84A	81%
RPS-C2-10-15	15V	0.6A	82%
RPS-C2-10-24	24V	0.42A	84%



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -10~+50℃
- Dimension 22.5*90*100MM
- Weight 0.19KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C2-20-5	5V	3A	76%
RPS-C2-20-12	12V	1.67A	80%
RPS-C2-20-15	15V	1.34A	81%
RPS-C2-20-24	24V	1A	84%



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -10~+50℃
- Dimension 40*90*100MM
- Weight 0.3KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C2-40-5	5V	6A	78%
RPS-C2-40-12	12V	3.33A	86%
RPS-C2-40-24	24V	1.7A	88%
RPS-C2-40-48	48V	0.83A	88%



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -10~+50℃
- Dimension 40*90*100MM
- Weight 0.33KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C2-60-5	5V	10A	76%
RPS-C2-60-12	12V	5A	84%
RPS-C2-60-24	24V	2.5A	86%
RPS-C2-60-48	48V	1.25A	86%

RPS-C2-... Series Din Rail Power Supply



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 55*90*100MM
- Weight 0.42KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C2-100-12	12V	7.5A	83%
RPS-C2-100-15	15V	6.6A	83%
RPS-C2-100-24	24V	4.16A	86%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 55*90*100MM
- Weight 0.42KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C2-100-27	27V	3.7A	86%
RPS-C2-100-36	36V	2.7A	86%
RPS-C2-100-48	48V	2A	87%

RPS-C3-... series Din Rail Power Supply



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 17.5*90*54.5MM
- Weight 0.08KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C3-15-5	5V	2.4A	78%
RPS-C3-15-12	12V	1.25A	83%
RPS-C3-15-24	24V	0.63A	84%
RPS-C3-15-48	48V	0.32A	85%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 35*90*54.5MM
- Weight 0.12KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C3-30-5	5V	3A	80%
RPS-C3-30-12	12V	2A	86%
RPS-C3-30-24	24V	1.5A	87%
RPS-C3-30-48	48V	0.75A	87%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 52.5*90*54.5MM
- Weight 0.19KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C3-60-5	5V	6.5A	82%
RPS-C3-60-12	12V	4.5A	85%
RPS-C3-60-24	24V	2.5A	88%
RPS-C3-60-48	48V	1.25A	88%



Features :

- Input Full Range 85~264VAC/120~370VDC 47~63Hz
- Working Temp. -10~+50℃
- Dimension 70*90*54.5MM
- Weight 0.27KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C3-100-12	12V	7.5A	86%
RPS-C3-100-15	15V	6.5A	86%
RPS-C3-100-24	24V	4.2A	88%
RPS-C3-100-48	48V	2.1A	88%

RPS-C5-... Series Power Supply



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -20~+70℃
- Dimension 99*82*30MM
- Weight 0.23KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C5-35-12	12V	3A	84%
RPS-C5-35-24	24V	1.5A	86%
RPS-C5-35-36	36V	1A	87%
RPS-C5-35-48	48V	0.8A	87%



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -20~+70℃
- Dimension 99*82*30MM
- Weight 0.23KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C5-50-12	12V	4.2A	84%
RPS-C5-50-24	24V	2.2A	86%
RPS-C5-50-36	36V	1.3A	87%
RPS-C5-50-48	48V	1.1A	87%



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -20~+70℃
- Dimension 99*82*30MM
- Weight 0.23KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C5-60-12	12V	5A	84%
RPS-C5-60-15	15V	4A	84%
RPS-C5-60-24	24V	2.5A	86%
RPS-C5-60-48	48V	1.25A	87%



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -20~+70℃
- Dimension 99*97*30MM
- Weight 0.3KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C5-75-12	12V	6A	86%
RPS-C5-75-24	24V	3.2A	87%
RPS-C5-75-36	36V	2A	88%
RPS-C5-75-48	48V	1.6A	88%



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -20~+70℃
- Dimension 129*97*30MM
- Weight 0.34KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C5-100-12	12V	8.5A	86%
RPS-C5-100-24	24V	4.5A	87%
RPS-C5-100-36	36V	2.7A	88%
RPS-C5-100-48	48V	2.3A	88%



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -20~+70℃
- Dimension 129*97*30MM
- Weight 0.34KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C5-120-12	12V	10A	86%
RPS-C5-120-15	15V	8A	86%
RPS-C5-120-24	24V	5A	87%
RPS-C5-120-48	48V	2.5A	87%



Features :

- Input Full Range
  85~264VAC/120~370VDC
  47~63Hz
- Working Temp. -20~+70℃
- Dimension 159*97*30MM
- Weight 0.48KGS
- 3 Years Warranty


Model	DC output	Current	Efficiency
RPS-C5-150-12	12V	12.5A	84%
RPS-C5-150-24	24V	6.5A	86%
RPS-C5-150-36	36V	4.1A	87%
RPS-C5-150-48	48V	3.3A	88%



Features :

- AC Input 90~132V/180~264V
  By Switch/47~63Hz
- Working Temp. -20~+70℃
- Dimension 215*115*30MM
- Weight 0.66KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C5-200-12	12V	17A	84%
RPS-C5-200-24	24V	8.8A	86%
RPS-C5-200-36	36V	5.5A	87%
RPS-C5-200-48	48V	4.4A	88%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -20~+70℃
- Dimension 215*115*30MM
- Weight 0.66KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C5-250-12	12V	20A	86%
RPS-C5-250-15	15V	16A	86%
RPS-C5-250-24	24V	10A	87%
RPS-C5-250-48	48V	5A	88%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -20~+70℃
- Dimension 215*115*30MM
- Weight 0.76KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C5-350-36	36V	9.7A	87%
RPS-C5-350-48	48V	7.3A	87%
RPS-C5-350-60	60V	5.83A	88%
RPS-C5-350-70	70V	5A	88%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -20~+70℃
- Dimension 215*115*50MM
- Weight 1KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C5-500-12	12V	40A	86%
RPS-C5-500-24	24V	20A	87%
RPS-C5-500-36	36V	14A	88%
RPS-C5-500-48	48V	10A	88%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -20~+70℃
- Dimension 215*115*30MM
- Weight 0.76KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C5-350-12	12V	29A	83%
RPS-C5-350-15	15V	23.2A	84%
RPS-C5-350-24	24V	14.6A	86%
RPS-C5-350-27	27V	12.9A	87%



Features :

- AC Input 90~132V/180~264V By Switch/47~63Hz
- Working Temp. -20~+70℃
- Dimension 215*115*30MM
- Weight 0.76KGS
- 3 Years Warranty

Model	DC output	Current	Efficiency
RPS-C5-400-12	12V	33A	83%
RPS-C5-400-15	15V	26.7A	84%
RPS-C5-400-24	24V	16.5A	85%
RPS-C5-400-48	48V	8.3A	86%

CHIKU®

For more info, please contact us

HUNTEC

SUZHOU HUNTEC INT'L TRADING CO., LTD.

Add.: 36 zijing street, Mudu Town, Wuzhong District,Suzhou, Jiangsu Province, China
Factory: Jiangxi Huntec Electrical Technology Co.,Ltd.
Add.:1829th Yangguang Avenue, Xinyu, Jiangxi Province, China

Email: info@cnhuntec.com
Tel: +86-0512-65122750
Website: www.cnhuntec.com
www.chikucontact.com